



800 Series

Hot-Water Pressure Washers

#1 in North America for High-Pressure Cleaning Equipment

Electric / Belt Drive

Upright, oil fired burner delivers high efficiency and maintains constant temperature using diesel fuel, kerosene or home-heating oil

50-ft. length of high-pressure hose for ease in cleaning around a large area

Hose-reel slot accepts swivel or stationary reels for ease in hose management and storage

Simple, easy-to-use control panel includes adjustable thermostat

Heater coil carries a 5-year warranty



Pressure relief valve protects the machine and user from thermal expansion

Stainless-steel coil skin provides extra durability to withstand the elements

Protective cabinet contains water resistant electrical box

Float tank helps maintain constant water pressure and flow while helping to prevent sediment from entering the machine's components

Forklift slots for easy lifting

Rust-proof, removable, non-contaminating polyethylene fuel tank includes fuel gauge in cap

Wide wheel base for stability, but 28" width easily fits through doors

12" solid rubber tires for easy maneuvering; eliminates risk of flats

Reliable, energy efficient **Hotsy Crossfire oil burner** is built to provide years of trouble free service.

Adjustable upstream detergent injection ensures high-pressure sudsing for better cleaning

On board **wand and cord storage**

Beefy casters for easy movement

35-ft. power cord with safety **Ground Fault Circuit Interrupter (GFCI breaker)**
*single phase only

FEATURES

- 4.0 - 5.0 GPM @ 2000 to 3000 PSI
- Hotsy Crossfire Oil Fired Burner
- 208V, 230V, 460V or 575V, 1PH or 3PH
- Belt Drive Pump

Easily removable **cover** provides protection and easy access to components



Hotsy-designed Triplex pumps carry a 7-year limited warranty

www.Hotsy.com

Nothing Cleans Like a Hotsy!

800 SERIES Hot-Water ELECTRIC Models

Oil-Fired 4.0 - 5.0 GPM @ 2000 to 3000 PSI Hotsy 7-Year Pump Warranty Belt Drive

Rugged design, easy maneuverability and massive cleaning power!

SPECIFICATIONS

BELT DRIVE

MODEL	GPM	PSI	HP	MOTOR RPM	VOLT/PH	AMP	FUEL	BTU/HR	PUMP MODEL	HOSE	SHIP WT
821	4.0	2300	6.2	3450	208/1	33	Oil	342,900	HHC506R.2	50'	632
842	4.0	2000	5	1725	208/3	20	Oil	342,900	HH406R.2	50'	622
843	4.0	2000	5	1725	230/1	29	Oil	342,900	HH406R.2	50'	622
844	4.0	2000	5	1725	230/3	19	Oil	342,900	HH406R.2	50'	622
845	4.0	2000	5	1725	460/3	10	Oil	342,900	HH406R.2	50'	691
851	4.0	3000	8.2	3450	208/1	44	Oil	342,900	HHC506R.2	50'	675
852	4.0	3000	7.5	1725	208/3	25	Oil	342,900	HH406R.2	50'	665
853	4.0	3000	7.5	1725	230/1	37	Oil	342,900	HH406R.2	50'	665
854	4.0	3000	7.5	1725	230/3	25	Oil	342,900	HH406R.2	50'	665
855	4.0	3000	7.5	1725	460/3	14	Oil	342,900	HH406R.2	50'	665
856	4.0	3000	8.2	3450	575/3	11	Oil	342,900	HHC506R.2	50'	680
873	5.0	3000	10	1725	230/1	42	Oil	395,452	HH406R.2	50'	670
874	5.0	3000	10	1770	230/3	29	Oil	395,452	HH406R.2	50'	675

Dimensions: 51"l x 28"w x 51"h



Clean better with Hotsy detergents

Hotsy pressure washers clean best when matched with specially

formulated Hotsy detergents. More than 40 liquids and powders meet every cleaning need imaginable. Nearly all contain Hotsy's exclusive advanced-formula HCC additives to help prevent scale build-up and to fight corrosion in your equipment. Most Hotsy detergents are USDA and Canadian Agriculture approved. All are highly concentrated, so a little goes a long way.

Spend some time with a Hotsy Expert

Hotsy has more than 160 local dealers in North America, all factory-trained to properly evaluate your high-pressure cleaning needs.

Over 80% of Hotsy's dealers have been supporting Hotsy systems for more than 20 years.

Rely on our network of seasoned service professionals for the safest, most effective and most efficient solution to your specific cleaning need.



OPTIONS for 800 SERIES

- 8" Oil-Fired Draft Dampener *barometric; prevent backdrafts; keeps cold air out*
- Auto Start / Stop, Thermal Shutdown or Time Delay Shutdown
- Hose Reels & Hose Reel Brackets

Hotsy Accessories customize your application for top performance

Telescoping wands extend to 24-ft. to reach high places without scaffolding



High-pressure turbo nozzles for faster cleaning

360° Pivot and non-pivot hose reels keep hose neatly stored and shop areas safe

Rotary surface cleaner attaches to your pressure washer; reduces overspray and zebra striping



hotsy Nothing Cleans Like a Hotsy!

Tel: (800) 525-1976 Fax: (888) 880-9631
 www.Hotsy.com email: info@Hotsy.com
 P/N 9.801-490.0 Effective 3/13 Specifications & product descriptions subject to change without notice. ©2013 Hotsy
 A member of KÄRCHER North America



NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We attempt to keep our machine performance within ± 10% of listed specifications.

Distributed by: